

KITECH HYDROGEN SYSTEMS

KNOX SERIES ELECTROLYSERS

Knox 20

K 20 are designed for small commercial vehicles with HHO production range of 1.5 to 3 Litres per minute. Suitable for engines from 1500cc to 3000cc for maximum savings. Operates on 12V with maximum current of 33 Amps.

Knox 30

K 30 are designed for mid size commercial vehicles with HHO production range of 2.5 to 4.5 Litres per minute. Suitable for engines from 3000cc to 4500cc for maximum savings. Operates on 12V with maximum current of 40 Amps.

Knox 40

K 40 are designed for large commercial vehicles with HHO production range of 4 to 7 Litres per minute. Suitable for engines from 4000cc to 6500cc for maximum savings. Operates on 12V with maximum current of 33 Amps.

Units can be deployed on larger cc engines with varying savings. KiTech R&D keeps improving the models and HHO capacity may keep changing for higher volumes.



Highest HHO Production

Knox Hydrogen Fuel Systems are patented and boast of their ability to produce highest amount of hydrogen gas within the limited voltage supplies of any vehicle.

KiTech Hydrogen Systems are complete solution to any vehicle running on fossil fuel to reduce emissions and improve fuel efficiency significantly.

Knox Electrolysers have three cells each with different configuration in each cell. Using innovative Stainless plate array in their cells the design ensures highest hydrogen separation from distilled water. Supported by a pump, DC Supply system, water tank, a bubbler and a protective box casing, Kitech Hydrogen Fuel Systems are the best answer to emission control and fuel reduction for every vehicle running on fossil Fuels.



KiTech Hydrogen Systems Pte. Limited
160, Robinson Road, #14-04
Singapore, 06891